



 **MAXUS**

**eDELIVER 9**  
100% ELECTRIC VEHICLE



# MAXUS eDELIVER 9 VARIANTS

## Specifications

MAXUS eDELIVER 9 N1 VARIANTS <3500kg	L2H2	L3H2	L3H2	L3H3	L3H3	L3H2 Crew Van	L3H3 Crew Van
	Capacity (kWh) 77kWh	Capacity (kWh) 77kWh	Capacity (kWh) 88kWh	Capacity (kWh) 77kWh	Capacity (kWh) 88kWh	Capacity (kWh) 77kWh	Capacity (kWh) 77kWh
Sliding door	Single/Double	Single/Double	Single/Double	Single/Double	Single/Double	Single/Double	Single/Double
Battery capacity(kWh)	77	77	88	77	88	77	77
Driving wheel	FWD	FWD	FWD	FWD	FWD	FWD	FWD
GVW(kg)	3500	3500	3500	3500	3500	3500	3500
CVW(kg)	2460/2680	2520/2540	2590/2610	2580/2600	2650/2670	2520/2540	2580/2600
Payload(kg)	1040/1020	980/960	910/890	920/900	850/830	980/960	920/900
GVW axle load: front/rear (kg)	1660/1840	1740/1760	1740/1760	1750/1750	1750/1750	1740/1760	1750/1750
Max axle load: front/rear(kg)	1885/2350	1885/2350	1885/2350	1885/2350	1885/2350	1885/2350	1885/2350
GTM (kg)	4250	4250	4250	4250	4250	4250	4250
Towing capacity (Braked/Unbraked) (kg)	1500/750	1500/750	1500/750	1500/750	1400/750	1500/750	1500/750
Rated power/Max power (kW)	75/150	75/150	75/150	75/150	75/150	75/150	75/150
Rated torque/Max torque (N.m)	170/330	170/330	170/330	170/330	170/330	170/330	170/330
Max speed(km/h)	100	100	100	100	100	100	100
Acceleration 0-50kmh/0-31mph (sec)	6.1	6.1	6	6.5	6.3	6.1	6.5
Acceleration 0-100kmh/0-62mph (sec)	18.3	18.3	16	19	16.5	18.3	19
Min turning diameter(m)	13.4±1	14.8±1	14.8±1	14.8±1	14.8±1	14.8±1	14.8±1
Approach angle/departure angle (CVW)	19.0/17.8	18.5/17.9	18.5/17.9	18.5/17.9	18.5/17.9	18.5/17.9	18.5/17.9
Approach angle/departure angle (GVW)	17.3/15.1	16.7/15.5	16.7/15.5	16.7/15.5	16.7/15.5	16.7/15.5	16.7/15.5
Dimensions: length*width*height(mm)	5546*2062*2515	5940*2062*2515	5940*2062*2515	5940*2062*2730	5940*2062*2730	5940*2062*2515	5940*2062*2730
Wheel base (mm)	3366	3760	3760	3760	3760	3760	3760
Cargo volume (m³)	9.7	11	11	12.3	12.3	7.1	7.8
Dimensions of cargo space: length*width*height(mm)	3019*1800*1802	3413*1800*1802	3413*1800*1802	3413*1800*2019	3413*1800*2019	3413*1800*1802	3413*1800*2019
Max width cargo space between wheel arches(mm)	1366	1366	1366	1366	1366	1366	1366
Slide door width(mm)	1269	1269	1269	1269	1269	1269	1269
Slide door height(mm)	1570	1570	1570	1570	1570	1570	1570
Ground clearance of the front axle (mm)	180	173	173	173	173	173	173
Ground clearance of the rear axle (mm)	223	228	228	228	228	228	228
Ground clearance between axles (mm)	196	190	190	190	190	190	190
AC Charging time (5%~100%) (h)/ Charging power (kW) 25°, Three-Phase"	8.5h/11kw 4.5h/22kw (Optional)	8.5h/11kw 4.5h/22kw (Optional)	9.3h/11kw 5.2h/22kw (Optional)	8.5h/11kw 5.2h/22kw (Optional)	9.3h/11kw 5.2h/22kw (Optional)	8.5h/11kw 4.5h/22kw (Optional)	8.5h/11kw 4.5h/22kw (Optional)
•	51min/78kw	51min/78kw	51min/90kw	51min/78kw	51min/90kw	51min/78kw	51min/78kw
Energy consumption WLTC combined (kWh/100km)*	29.4~31.0	29.4~31.0	30.0~31.9	30.4~32.1	30.9~32.9	29.4~31.0	30.4~32.1
Range WLTC combined (km/mi)*	285~300/177~186	285~300/177~186	320~340/199~211	275~290/170~180	310~330/193~205	285~300/177~186	275~290/170~180
Range WLTC city (km/mi)*	380~400/170~180	380~400/170~180	425~445/364~377	365~385/226~239	410~430/255~267	380~400/170~180	365~385/226~239
Tyre	215/75R16	215/75R16	215/75R16	215/75R16	215/75R16	215/75R16	215/75R16

\*Estimated range & energy consumption under WLTC test standard. Actual range & energy consumption varies with conditions such as temperature, operation of air conditioner, driving mode, route conditions, battery age and loss of capacity.

# MAXUS eDELIVER 9 VARIANTS

## Specifications

MAXUS eDELIVER 9 N1 VARIANTS <3500kg	L2H2	L3H2	L3H2	L3H3	L3H3	L3H2 Crew Van	L3H3 Crew Van
	Capacity (kWh) 77kWh	Capacity (kWh) 77kWh	Capacity (kWh) 88kWh	Capacity (kWh) 77kWh	Capacity (kWh) 88kWh	Capacity (kWh) 77kWh	Capacity (kWh) 77kWh
Battery thermal management: liquid cooling & liquid heating	S	S	S	S	S	S	S
V2L exterior	S	S	S	S	S	S	S
V2L interior	O	O	O	O	O	O	O
11kw AC charger & EPTO (high voltage power take-off)*	S	S	S	S	S	S	S
22kw AC charger & DCDC (low voltage power take-off)*	O	O	O	O	O	O	O
Charging wire: Mode 3, Three-Phase	S	S	S	S	S	S	S
LED headlights	S	S	S	S	S	S	S
LED tail lights	S	S	S	S	S	S	S
Front & rear fog lights	S	S	S	S	S	S	S
Single sliding door	S	S	S	S	S	S	S
Dual sliding door	O	O	O	O	O	O	O
Rear wing doors with 180°hinges	S	-	-	-	-	-	-
Rear wing doors with 236°hinges	-	S	S	S	S	S	S
Alloy wheel 6.5Jx16	S	S	S	S	S	S	S
Power heated exterior mirrors	S	S	S	S	S	S	S
Power side step**	O	O	O	O	O	O	O
Roof rack mounting holes	-	S	S	-	-	S	-
Microfiber leather multifunctional steering wheel with heated steering wheel	S	S	S	S	S	S	S
Anti-glare interior mirror	S	S	S	S	S	S	S
Column-mounted shifter	S	S	S	S	S	S	S
Heated front seats	O	O	O	O	O	O	O
LED front reading light	S	S	S	S	S	S	S
Power front windows (one click up & down)	S	S	S	S	S	S	S

\*When you choose 22kw AC charger & DCDC, EPTO is not available. EPTO is the high voltage power take-off, and its voltage range is about 260V~440V. DCDC is the low voltage power take-off, and its voltage is about 14V.

\*\*When you choose Dual sliding door, Power side step can not be chosen.

\*\*\*1 light for L2 models, 2 lights for L3 models

\*\*\*\*The controller can not work until installing a connecting cable through after-sales

# MAXUS eDELIVER 9 VARIANTS

## Specifications

MAXUS eDELIVER 9 N1 VARIANTS <3500kg	L2H2	L3H2	L3H2	L3H3	L3H3	L3H2 Crew Van	L3H3 Crew Van
	Capacity (kWh) 77kWh	Capacity (kWh) 77kWh	Capacity (kWh) 88kWh	Capacity (kWh) 77kWh	Capacity (kWh) 88kWh	Capacity (kWh) 77kWh	Capacity (kWh) 77kWh
Automatic windshield wiper	S	S	S	S	S	S	S
LED cargo lights***	S	S	S	S	S	S	S
Automatic air conditioner	O	O	O	O	O	O	O
12.3" touch screen with MP5 & USB & Bluetooth & Carplay & Android Auto	S	S	S	S	S	S	S
4 speakers	S	S	S	S	S	S	S
DAB	S	S	S	S	S	S	S
Tyre pressure monitoring system	S	S	S	S	S	S	S
6 airbags (front,side,curtain) for driver & front passengers	S	S	S	S	S	S	S
ECall	S	S	S	S	S	S	S
Safety belt reminder	S	S	S	S	S	S	S
Rear view camera	S	S	S	S	S	S	S
360 camera	O	O	O	O	O	O	O
Front radar	S	S	S	S	S	S	S
Rear radar	S	S	S	S	S	S	S
ESP+EBA+HHC	S	S	S	S	S	S	S
EPB	S	S	S	S	S	S	S
Full-speed ACC	S	S	S	S	S	S	S
Automatic emergency braking system	S	S	S	S	S	S	S
Lane departure warning & lane keeping assist system	S	S	S	S	S	S	S
Blind spot detection & door-open warning system	S	S	S	S	S	S	S
Lane change assist	S	S	S	S	S	S	S
Speed limit information	S	S	S	S	S	S	S
Driver monitor system	S	S	S	S	S	S	S
Adjustable overspeed warning	S	S	S	S	S	S	S
Keyless start	S	S	S	S	S	S	S
2 smart keys	S	S	S	S	S	S	S
Rear trailer tow interface with controller****	S	S	S	S	S	S	S
Removable front tow hook	S	S	S	S	S	S	S

\*When you choose 22kw AC charger & DCDC, EPTO is not available. EPTO is the high voltage power take-off, and its voltage range is about 260V~440V. DCDC is the low voltage power take-off, and its voltage is about 14V.

\*\*When you choose Dual sliding door, Power side step can not be chosen.

\*\*\*1 light for L2 models, 2 lights for L3 models

\*\*\*\*The controller can not work until installing a connecting cable through after-sales

# MAXUS eDELIVER 9 VARIANTS

## Specifications

MAXUS eDELIVER 9 N1 VARIANTS <3500kg Chassis Cab	L3CC	L3CC	L4CC	L4CC
	77 kWh	88 kWh	77 kWh	88 kWh
<b>DIMENSIONS &amp; CAPACITIES</b>				
Number of seats	3	3	3	3
Overall length (mm)	6200	6200	6680	6680
Overall width (mm)	2052	2052	2052	2052
Overall height (mm)	2310	2310	2310	2310
Wheel base (mm)	3760	3760	4048	4048
Maximum permissible length (mm)	6529	6529	6835	6835
Maximum permissible width (mm)	2136	2136	2136	2136
Maximum permissible height (mm)	2960	2960	2960	2960
Ground clearance of the front axle (mm)	183	183	169	169
Ground clearance of the rear axle (mm)	238	238	246	246
Ground clearance between axles (mm)	200	200	187	187
<b>WEIGHTS &amp; PAYLOAD</b>				
GVW(kg)	3500	3500	3500	3500
CVW(kg)	2155	2215	2165	2225
Payload:GVW-CVW(kg)	1345	1285	1335	1275
GVW axle load: front/rear(kg)	1660~1740/1840~1760	1685~1740/1815~1760	1715~1775/1785~1725	1735~1800/1765~1700
Max axle load: front/rear(kg)	1885/2350	1885/2350	1885/2350	1885/2350
GTM (kg)	4250	4250	4250	4250
Towing capacity (Braked/Unbraked) (kg)	1500/750	1500/750	1500/750	1500/750
<b>BATTERY &amp; CHARGING</b>				
Battery capacity(kWh)	77	88	77	88
Range WLTP combined (km/mi)*	189~288/118~179	214~339/133~211	187~287/116~178	211~334/131~208
Range WLTP city (km/mi)*	291~403/181~250	366~483/227~300	290~402/180~250	364~480/226~298
Energy consumption WLTP combined (kWh/100km/62mi)*	29.6~43.5	29.0~42.7	29.7~43.7	29.4~43.0
AC Charging time (5%~100%) (h)/Charging power (kW) Three-Phase	8.5h/11kw(S) 4.5h/22kw(O)	9.3h/11kw(S) 5.2h/22kw(O)	8.5h/11kw(S) 4.5h/22kw(O)	9.3h/11kw(S) 5.2h/22kw(O)
DC Charging time (10%~80%) (h)/Charging power (kw)	51min/78kw	51min/90kw	51min/78kw	51min/90kw
Battery thermal management: liquid cooling & liquid heating	S	S	S	S
11kw AC charger & EPTO(high voltage power take-off)**	S	S	S	S
22kw AC charger & DCDC(low voltage power take-off)**	O	O	O	O
Charging wire: Mode 3, Three-Phase	S	S	S	S
V2L exterior	S	S	S	S

MAXUS eDELIVER 9 N1 VARIANTS <3500kg Chassis Cab	L3CC	L3CC	L4CC	L4CC
	77 kWh	88 kWh	77 kWh	88 kWh
<b>POWER &amp; DRIVING</b>				
Driving wheel	FWD	FWD	FWD	FWD
Rated power/Max power (kW)	75/150	75/150	75/150	75/150
Rated torque/Max torque (N.m)	170/330	170/330	170/330	170/330
Max speed (kmh/mph)	100/62	100/62	100/62	100/62
Min turning diameter (m)	14.8±1	14.8±1	15.8±1	15.8±1
Approach angle/departure angle (CVW) (°)	17.9/17.2	17.9/17.2	17.8/15.2	17.8/15.2
Approach angle/departure angle (GVW) (°)	17.3/13.1	17.3/13.1	16.4/12.2	16.4/12.2
Tyre	215/75R16	215/75R16	215/75R16	215/75R16
<b>EXTERIOR</b>				
LED headlights	S	S	S	S
Front & rear fog lights	S	S	S	S
Alloy wheel 6.5Jx16	O	O	O	O
Power heated exterior mirrors	S	S	S	S
Removable front tow hook	S	S	S	S
Rear trailer tow interface	S	S	S	S
<b>INTERIOR &amp; COMFORT</b>				
Microfiber leather multifunctional steering wheel with heated steering wheel	S	S	S	S
Anti-glare interior mirror	S	S	S	S
Column-mounted shifter	S	S	S	S
Heated front seats	O	O	O	O
LED front reading light	S	S	S	S
Power front windows (one click up & down)	S	S	S	S
Automatic windshield wiper	S	S	S	S
Automatic air conditioner	O	O	O	O
12.3" touch screen with MP5 & USB & Bluetooth & Carplay & Android Auto	S	S	S	S
4 speakers	S	S	S	S
DAB	S	S	S	S
Keyless start	S	S	S	S
2 smart keys	S	S	S	S

MAXUS eDELIVER 9 N1 VARIANTS <3500kg Chassis Cab	L3CC	L3CC	L4CC	L4CC
	77 kWh	88 kWh	77 kWh	88 kWh
<b>SAFETY &amp; SECURITY</b>				
Tyre pressure monitoring system	S	S	S	S
6 airbags (front,side,curtain) for driver & front passengers	S	S	S	S
ECall	S	S	S	S
Safety belt reminder	S	S	S	S
Front radar	S	S	S	S
Driver Assistance				
ESP+EBA+HHC	S	S	S	S
EPB	S	S	S	S
Full-speed ACC	S	S	S	S
Automatic emergency braking system	S	S	S	S
Lane departure warning & lane keeping assist system	S	S	S	S
Speed limit information	S	S	S	S
Driver monitor system	S	S	S	S
Adjustable overspeed warning	S	S	S	S

\*Estimated range & energy consumption under EU WLTP test standard. Actual range & energy consumption varies with conditions such as size&shape of cargo box, temperature, operation of air conditioner, driving mode, route conditions, battery capacity loss and loading mass. When installing a tall cargo box, it is advisable to install a shroud to reduce wind resistance.

\*\*When you choose 22kw AC charger & DCDC, EPTO is not available. The available power of DCDC is 2.5kw. The peak power of EPTO is 5kw.

MAXUS eDELIVER 9 N2 VARIANTS 4250kg	L3H2	L3H3
	Capacity (kWh) 88kWh	Capacity (kWh) 88kWh
<b>DIMENSIONS &amp; CAPACITIES</b>		
Number of seats	3	3
Sliding door	Single	Single
Rear Wheels	Single	Single
Overall length (mm)	5940	5940
Overall width (mm)	2062	2062
Overall height (mm)	2555	2770
Wheel base (mm)	3760	3760
Cargo volume (m <sup>3</sup> )	11	12.3
Loadspace length (mm)	3413	3413
Loadspace width (mm)	1800	1800
Loadspace height (mm)	1802	2019
Max loadspace width between wheel arches (mm)	1366	1366
Slide door width (mm)	1269	1269
Slide door height (mm)	1570	1570
Ground clearance of the front axle (mm)	179	178
Ground clearance of the rear axle (mm)	145	144
Ground clearance between axles (mm)	145	144
<b>WEIGHTS &amp; PAYLOAD</b>		
GVW (kg)	4250	4250
CVW (kg)	2720	2780
Payload: GVW-CVW (kg)	1530	1470
GVW axle load: front/rear (kg)	1750/2500	1760/2490
Max axle load: front/rear (kg)	1950/2760	1950/2760
GTM (kg)	5000	5000
Towing capacity (Braked/Unbraked) (kg)	2000/750	2000/750



MAXUS eDELIVER 9 N2 VARIANTS 4250kg	L3H2	L3H3
	Capacity (kWh) 88kWh	Capacity (kWh) 88kWh
<b>BATTERY &amp; CHARGING</b>		
Battery capacity (kWh)	88	88
Range WLTP combined (km/mi)*	300~330/186~205	288~318/179~198
Range WLTP city (km/mi)*	381~419/237~260	369~407/229~253
Energy consumption WLTP combined (kWh/100km)*	29.1~32.0	30.6~33.7
AC Charging time (5%~100%) (h)/Charging power (kW) Three-Phase	9.3h/11kw(S) 5.2h/22kw(O)	9.3h/11kw(S) 5.2h/22kw(O)
DC Charging time (10%~80%) (h)/Charging power (kw)	51min/90kw	51min/90kw
Battery thermal management□liquid cooling & liquid heating	S	S
11kw AC charger & EPTO(high voltage power take-off)**	S	S
22kw AC charger & DCDC(low voltage power take-off)**	O	O
Charging wire: Mode 3, Three-Phase	S	S
V2L exterior	S	S
V2L interior	O	O
<b>POWER &amp; DRIVING</b>		
Driving wheel	RWD	RWD
Rated power/ Max power (kW)	70/170	70/170
Rated torque/ Max torque(N.m)	170/330	170/330
Max speed(kmh/mph)	90/56	90/56
Acceleration 0-50kmh/0-31mph(sec)	6.5	7.0
Acceleration 0-100kmh/0-62mph(sec)	21	22
Min turning diameter(m)	14.1±1	14.1±1
Approach angle/departure angle (CVW) (°)	19.6/20.4	19.5/20.3
Approach angle/departure angle (GVW) (°)	17.1/14.7	17.0/14.6
Tyre	235/65R16	235/65R16
<b>EXTERIOR</b>		
LED headlights	S	S
LED tail lights	S	S
Front & rear fog lights	S	S
Single sliding door	S	S
Rear wing doors with 236°hinges	S	S
Alloy wheel 6.5Jx16	O	O
Power heated exterior mirrors	S	S
Power side step	O	O
Roof rack mounting points	S	-
Removable front tow hook	S	S
Rear trailer tow interface with controller***	S	S

MAXUS eDELIVER 9 N2 VARIANTS 4250kg	L3H2	L3H3
	Capacity (kWh) 88kWh	Capacity (kWh) 88kWh
<b>INTERIOR &amp; COMFORT</b>		
Microfiber leather multifunctional steering wheel with heated steering wheel	S	S
Anti-glare interior mirror	S	S
Column-mounted shifter	S	S
Heated front seats	O	O
LED front reading light	S	S
Power front windows (one click up & down)	S	S
Automatic windshield wiper	S	S
LED cargo lights	S	S
Automatic air conditioner	O	O
12.3" touch screen with MP5 & USB & Bluetooth & Carplay & Android Auto	S	S
4 speakers	S	S
DAB	S	S
Keyless start	S	S
2 smart keys	S	S
<b>SAFETY &amp; SECURITY</b>		
Tyre pressure monitoring system	S	S
6 airbags (front,side,curtain) for driver & front passengers	S	S
Safety belt reminder	S	S
Rear view camera	S	S
360 camera	O	O
Front radar	S	S
Rear radar	S	S
<b>DRIVER ASSISTANCE</b>		
ESP+EBA+HHC	S	S
EPB	S	S
Full-speed ACC	S	S
Automatic emergency braking system	S	S
Lane departure warning & lane keeping assist system	S	S
Blind spot detection & door-open warning system & blind spot information system & moving off information system	S	S
Lane change assist	S	S
Speed limit information	S	S
Driver monitor system	S	S
Adjustable overspeed warning	S	S

\*Estimated range & energy consumption under EU WLTP test standard. Actual range & energy consumption varies with conditions such as temperature, operation of air conditioner, driving mode, route conditions, battery capacity loss and loading mass.

\*\*When you choose 22kw AC charger & DCDC, EPTO is not available. The available power of DCDC is 2.5kw. The peak power of EPTO is 5kw.

\*\*\*You need to buy and install connecting cables through after-sales to make the interface & controller work.

<b>MAXUS eDELIVER 9 N2 VARIANTS 4250kg Chassis Cab</b>	<b>L3H1CC</b>
	Capacity (kWh) 88kWh
<b>DIMENSIONS &amp; CAPACITIES</b>	
Number of seats	3
Rear Wheels	Single
Overall length (mm)	6200
Overall width (mm)	2052
Overall height (mm)	2310
Wheel base (mm)	3760
Maximum permissible length (mm)	6452
Maximum permissible width (mm)	2136
Maximum permissible height (mm)	2960
Ground clearance of the front axle (mm)	214
Ground clearance of the rear axle (mm)	142
Ground clearance between axles (mm)	142
<b>WEIGHTS &amp; PAYLOAD</b>	
GVW(kg)	4250
CVW(kg)	2310
Payload: GVW-CVW(kg)	1940
GVW axle load: front/rear(kg)	1500~1555/2695~2750
Max axle load: front/rear(kg)	1950/2760
GTM (kg)	5000
Towing capacity (Braked/Unbraked) (kg)	2000/750
<b>BATTERY &amp; CHARGING</b>	
Battery capacity(kWh)	88
Range WLTP combined (km/mi)*	198~286/123~178
Range WLTP city (km/mi)*	294~409/183~254
Energy consumption WLTP combined (kWh/100km/62mi)*	33.0~45.4
AC Charging time (5%~100%) (h)/Charging power (kW) Three-Phase	9.3h/11kw(S) 5.2h/22kw(O)
DC Charging time (10%~80%) (h)/Charging power (kw)	51min/90kw
Battery thermal management□liquid cooling & liquid heating	S
11kw AC charger & EPTO(high voltage power take-off)**	S
22kw AC charger & DCDC(low voltage power take-off)**	O
Charging wire: Mode 3, Three-Phase	S
V2L exterior	S

POWER & DRIVING		SAFETY & SECURITY	
Driving wheel	RWD	Tyre pressure monitoring system	S
Rated power/ Max power (kW)	70/170	6 airbags (front,side,curtain) for driver & front passengers	S
Rated torque/ Max torque(N.m)	170/330	Safety belt reminder	S
Max speed(kmh/mph)	90/56	Front radar	S
Min turning diameter(m)	14.1±1	Driver Assistance	
Approach angle/departure angle (CVW) (°)	19.6/20.4	ESP+EBA+HHC	S
Approach angle/departure angle (GVW) (°)	17.1/14.7	EPB	S
Tyre	235/65R16	Full-speed ACC	S
EXTERIOR		Automatic emergency braking system	S
LED headlights	S	Lane departure warning & lane keeping assist system	S
Front & rear fog lights	S	Blind spot information system & moving off information system	S
Alloy wheel 6.5Jx16	O	Speed limit information	S
Power heated exterior mirrors	S	Driver monitor system	S
Removable front tow hook	S	Adjustable overspeed warning	S
Rear trailer tow interface	S		
Interior & Comfort			
Microfiber leather multifunctional steering wheel with heated steering wheel	S		
Anti-glare interior mirror	S		
Column-mounted shifter	S		
Heated front seats	O		
LED front reading light	S		
Power front windows (one click up & down)	S		
Automatic windshield wiper	S		
Automatic air conditioner	O		
12.3" touch screen with MP5 & USB & Bluetooth & Carplay & Android Auto	S		
4 speakers	S		
DAB	S		
Keyless start	S		
2 smart keys	S		

\*Estimated range & energy consumption under EU WLTP test standard. Actual range & energy consumption varies with conditions such as size&shape of cargo box, temperature, operation of air conditioner, driving mode, route conditions, battery capacity loss and loading mass. When installing a tall cargo box, it is advisable to install a shroud to reduce wind resistance.

\*\*When you choose 22kw AC charger & DCDC, EPTO is not available. The available power of DCDC is 2.5kw. The peak power of EPTO is 5kw.